


WH-WXG12ME8 + WH-CME8



Aquarea M Series, the modular heat pump concept of Panasonic

Introducing M Series T-CAP, the latest generation of Aquarea air to water heat pumps with R290. Flexible hydraulic installation, 75°C water outlet down to -15°C outdoor, suitable for retrofit and new buildings.

[FIND OUT MORE](#)



Aquarea Service Cloud. Control for today and for the future

[FOR END USER](#)

[FOR INSTALLERS / MAINTENANCE](#)



Aquarea Quick Selector

Helping you to find the Aquarea Heat Pump for your home in just a few clicks!

[TRY THE AQUAREA QUICK SELECTOR](#)



AR Heat Pump Viewer

Interested to see how a Panasonic Aquarea Heat Pump looks in your home?
Try the new Panasonic AR projector, utilising augmented reality!

[TRY THE AQUAREA AR HEAT PUMP VIEWER](#)

**T-CAP stand-alone outdoor M Series
with control module 1 phase - 3
phase · R290**

12 kW

Outdoor unit		WH-WXG12ME8
Heating capacity (A +7°C, W 35°C)	kW	12,00
COP (A +7°C, W 35°C)		5,06
Heating capacity (A +7°C, W 55°C)	kW	12,00
COP (A +7°C, W 55°C)		3,23
Heating capacity (A +2°C, W 35°C)	kW	12,00
COP (A +2°C, W 35°C)		3,54
Heating capacity (A +2°C, W 55°C)	kW	12,00
COP (A +2°C, W 55°C)		2,42
Heating capacity (A -7°C, W 35°C)	kW	12,00
COP (A -7°C, W 35°C)		3,00
Heating capacity (A -7°C, W 55°C)	kW	12,00
COP (A -7°C, W 55°C)		2,17
Cooling capacity (A 35°C, W 7°C)	kW	9,00
EER (A 35°C, W 7°C)		3,61
Cooling capacity (A 35°C, W 18°C)	kW	12,00
EER (A 35°C, W 18°C)		5,26
Heating average climate. Seasonal energy efficiency (W 35°C / W 55°C)	SCOP	5,00 / 3,46
Heating average climate. Seasonal energy efficiency (W 35°C / W 55°C)	ηs %	197 / 135
Heating average climate. Energy class (W 35°C / W 55°C) (1)	A+++ to D	A+++ / A++
Heating warm climate. Seasonal energy efficiency (W 35°C / W 55°C)	SCOP	6,47 / 4,34
Heating warm climate. Seasonal energy efficiency (W 35°C / W 55°C)	ηs %	256 / 171
Heating warm climate. Energy class (W 35°C / W 55°C) (1)	A+++ to D	A+++ / A+++
Heating cold climate. Seasonal energy efficiency (W 35°C / W 55°C)	SCOP	4,31 / 3,26
Heating cold climate. Seasonal energy efficiency (W 35°C / W 55°C)	ηs %	169/127
Heating cold climate. Energy class (W 35°C / W 55°C) (1)	A+++ to D	A++ / A++

**T-CAP stand-alone outdoor M Series
with control module 1 phase - 3
phase · R290**

12 kW

Outdoor dimension (Height)	mm	1.520
Outdoor dimension (Width)	mm	1.200
Outdoor dimension (Depth)	mm	430
Outdoor net weight	kg	161
A class pump (Number of speeds)		Variable speed
A class pump (Input power Min)	W	30
A class pump (Input power Max)	W	175
Heating water flow ($\Delta T=5$ K, 35°C)	L/min	34,4
Operation range - Outdoor ambient (Heat)	°C	-28 ~ +35
Operation range - Outdoor ambient (Cool)	°C	+10 to +43
Water outlet (Heat)	°C	25 to 75
Water outlet (Cool)	°C	5 to 20
Indoor dimension (Height)	mm	450
Indoor dimension (Width)	mm	450
Indoor dimension (Depth)	mm	117
Indoor net weight	kg	7

Complementary products

